

Capital Tape Co, Inc
4920 Commerce Parkway #11
Cleveland, OH 44128
Fax: 216.292.3435



9228 / 9228BK PE Foam Tape – Rubber Adhesive

Product description:

1/8" thick polyethylene closed cell foam coated both sides with a permanent rubber-based adhesive available in white or black. The adhesives are protected by a durable, polycoated densified kraft liner. This liner is specifically designed to provide tear resistance and easy removability.

Physical properties:

Performance Test	Test Method	Lbs./in. Liner/Unwind
Loop Tack (stainless steel)	PSTC-16-Method A	12.0/12.0
Peel Adhesion 1 mil. PET Backed (30 min. dwell – stainless steel)	PSTC-101-Method A	12.0/12.0
Tensile (MD/CD)	ASTM-D882	145/105
Elongation (MD/CD)	ASTM-D882	339% / 308%

Shear Resistance – 1 kg.

PSTC-107-Method A

75+ hours to fail

Service Temperature:

Application:

50° F to 150°F

End use:

0°F to 180°F

These are approximate values and do not constitute warranty that products are fit for a particular purpose. The customer is advised to fully determine the suitability of these products for his intended use. These products conform to published specifications, if any, and the products are merchantable. Test data contained herein is believed to be reliable but unless specifically stated are not to be taken as specifications for products.