

CT1010

SWIRL-FREE MEDIUM DENSITY PVC FOAM TAPE



INDUSTRY **AUTOMOTIVE** **RECREATIONAL VEHICLES** GLAZING CONSTRUCTION DETAILING GASKETING ACOUSTICS LOG HOME MOUNTING PROTECTIVE

TAPE OVERVIEW

Aggressive, pressure-sensitive adhesive on one side of a medium density, closed cell foam. Formulated to resist twisting and tearing, these tapes are popular in insulating and sealing products, ideal for applications in RV's and Semitrailers.

- **Swirl-free/warp-free: It won't distort when penetrated by fasteners**
- **Flame resistant under FMVSS 302**
- **Seals out light, water, and dust**
- **Ideal for mechanical and electronic**
- **Allows for easy die-cutting**
- **Conforms to irregular surfaces**
- **Ideal applications: Recreational and off-road vehicles, vehicle overlap/truck roofline seals, die-cut gaskets, modular walls, railroad cars, marine, outdoor lighting fixtures and metal farm buildings, corrugated panels, lap joints**

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	9-10 lbs./cu. ft.
Hardness (Shore OO)	ASTM D-2240	35
Force to Compress (@ 25%)	ASTM D-1667	4 PSI
Tensile Strength	ASTM D-412	40 PSI min
Percent Elongation	ASTM D-412	140% min
Compression Set	LTM-028	10% max
Low Temperature Flex	ASTM D-2136	No cracking
Recommended Service Temp. 12 month shelf life	-30°F to 200°F -35°C to 90°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.



WE CUT TAPE.

Learn more at capitaltape.com