

# CT610

LOW DENSITY PVC FOAM TAPE



INDUSTRY **AUTOMOTIVE** RECREATIONAL VEHICLES **GLAZING** CONSTRUCTION DETAILING GASKETING ACOUSTICS LOG HOME MOUNTING PROTECTIVE

## TAPE OVERVIEW

A closed-cell, low-density PVC foam tape manufactured for use in applications requiring dust, light, and water-tight seals, from electronics, weatherstripping, and recreational vehicles.

- Low force compression, positive seal
- Cold resistant, will not crack
- High flexibility for corners & curves
- Seals out light, water, and dust
- Ideal for mechanical and electronic
- Great for curtain walls, retail walls
- Ideal applications: Recreational/off-road vehicles, busses, retail weatherstripping and curtain wall, pneumatic seal, refrigeration, HVAC and electronic cabinet sealing, concrete walls (precast), telecommunications, environmentally-controlled rooms



### SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

## TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	6 lbs./cu. ft.
Hardness (Shore OO)	ASTM D-2240	18
Compression Deflection (@ 25%)	ASTM D-1667	1.7 PSI
Compression Set	ASTM D-1667	15% max
Tensile Strength	ASTM D-412	18 PSI min
Dimensional Stability	ASTM D-1667	5% max
Low Temperature Flex	ASTM D-2136	No cracking
Recommended Service Temp. 12 month shelf life	-40°F to 180°F -35°C to 90°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	



**WE CUT TAPE.**

Learn more at [capitaltape.com](http://capitaltape.com)