

CT710

LOW-DENSITY CLOSED-CELL PVC FOAM TAPE



INDUSTRY AUTOMOTIVE RECREATIONAL VEHICLES **GLAZING** CONSTRUCTION DETAILING GASKETING ACOUSTICS LOG HOME MOUNTING PROTECTIVE

TAPE OVERVIEW

The CT710 tape is a closed-cell, PVC foam tape manufactured for use in applications requiring positive seals on irregular surfaces, or when flex and conformability to seal tight radius curves are critical considerations.

- Closed-cell PVC foam
- Lightweight, strong, and resilient
- Easy to compress and conformable
- Controls sound transmission and vibration
- Ideal for acoustical applications
- Excellent resistance to fungi, oxidation, and weather



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	7 lbs./cu. ft.
Hardness (Shore OO)	ASTM D-2240	15
Compression Deflection (@ 25%)	ASTM D-1667	1.0 PSI
Compression Set	ASTM D-1667	19% max
Tensile Strength	ASTM D-412	25 PSI
Percent Elongation	ASTM D-412	150
Low Temperature Flex	ASTM D-2136	No cracking
Recommended Service Temp. 12 month shelf life	-30°F to 200°F -35°C to 90°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	



WE CUT TAPE.

Learn more at capitaltape.com