

CTA710

LIGHT DENSITY PVC FOAM TAPE

CapitalTape
A family business, since 1990 



INDUSTRY **AUTOMOTIVE** RECREATIONAL VEHICLES GLAZING CONSTRUCTION DETAILING GASKETING **ACOUSTICS** LOG HOME MOUNTING PROTECTIVE

TAPE OVERVIEW

An automotive-grade, closed-cell PVC foam tape made for applications requiring positive seals on irregular surfaces, or when flex and conformability to seal tight radius curves are critical considerations.

- Closed-cell PVC foam
- Easy to compress and conformable
- Strong and resilient
- Self-extinguishing
- Meets FMVSS 302A standards
- Controls sound and vibration
- Ideal for acoustical applications
- Auto-certified foam, meets standards for GM spec GMW 15473 Class 2 Type 2, Chrysler spec MS-AY-500 Type 7, and Ford ESB-M3G102-A



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	7 lbs./cu. ft.
Hardness (Shore OO)	ASTM D-2240	15
Compression Deflection (@ 25%)	ASTM D-1667	1.0 PSI
Compression Set	ASTM D-1667	19% Max
Tensile Strength	ASTM D-412	25 PSI
Percent Elongation	ASTM D-412	150
Low Temperature Flex	ASTM D-2136	No cracking
Recommended Service Temp. 12 month shelf life	-30°F to 200°F -35°C to 90°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	

MEMBER
NGA
NATIONAL GLASS ASSOCIATION

FMVSS 302A
Federal Motor Vehicle Safety
Standard No. 302
CAPITAL TAPE

 **A.A.M.A.**
CERTIFIED 810.1-92

WE CUT TAPE.

Learn more at capitaltape.com

1-888-888-TAPE

service@capitaltape.com

4920 Commerce Parkway #11, Cleveland, OH 44128