

# V410

ULTRA-LOW DENSITY CLOSED-CELL PVC FOAM TAPE



INDUSTRY AUTOMOTIVE RECREATIONAL VEHICLES GLAZING CONSTRUCTION DETAILING GASKETING **ACOUSTICS** LOG HOME MOUNTING PROTECTIVE

## TAPE OVERVIEW

The V410 from Capital Tape is a general purpose, closed-cell PVC foam tape manufactured for use in applications requiring positive seals on irregular surfaces, or when flex and conformability to seal tight radius curves are critical considerations.

- **Conforms to irregular surfaces**
- **Ultra flexible to seal tight radius curves**
- **Easy to compress and conformable but still strong and resilient**
- **An alternative to low-density reeled/spooled urethane foams**
- **Excellent resistance to fungi**
- **Excellent resistance to weather**
- **Excellent resistance to oxidation**



### SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

## TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	4 lbs./cu. ft.
Force to Compress (@ 25%)	ASTM D-1667	0.3 PSI/24 kPa
Compression Set (@ 25%)	ASTM D-1667	5%
Tensile Strength	ASTM D-412	12 PSI/82.7 kPa
Percent Elongation	ASTM D-412	150
Thermal Conductivity	ASTM C-518	0.27
Recommended Service Temp. 12 month shelf life	-40°F to 180°F -40°C to 82°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	



**WE CUT TAPE.**

Learn more at [capitaltape.com](http://capitaltape.com)