

V810

LOW-DENSITY CLOSED-CELL PVC FOAM TAPE



INDUSTRY **AUTOMOTIVE** **RECREATIONAL VEHICLES** GLAZING CONSTRUCTION DETAILING GASKETING **ACOUSTICS** LOG HOME MOUNTING PROTECTIVE

TAPE OVERVIEW

The V810 Low-Density & Weatherstripping Tape from Capital Tape is an automotive-grade tape used when air- and moisture-tight seals on irregular surfaces are critical. Easy to compress, nearly impossible to destroy.

- Easy to compress and conformable
- Strong and resilient
- Ultra flexible to seal tight radius or irregular surfaces
- Excellent resistance to fungi, oxidation, and weather
- Fire rating: Meets/exceeds FMVSS 302A
- Self-Extinguishing



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

| | | |
|--|---------------------------------|----------------|
| Density | ASTM D-1667 | 8 lbs./cu. ft. |
| Hardness (Shore OO) | ASTM D-2240 | 25 |
| Force to Compress (@ 25%) | ASTM D-1667 | 2 PSI/14 kPa |
| Compression Set (@ 25%) | ASTM D-1667 | 4% |
| Tensile Strength | ASTM D-412 | 30 PSI/207 kPa |
| Peel Adhesion | ASTM D-1000 | 2 lbs |
| Water absorption (% by volume) | GTP | 1.0 |
| Percent Elongation | ASTM D-412 | 150 |
| Thermal Conductivity | ASTM C-518 | 0.27 |
| Recommended Service Temp. 12 month shelf life | -40°F to 180°F -40°C to 80°C | |
| Recommended Application Temperature | 50°F to 110°F 10°C to 45°C | |
| Fungi resistance | Excellent | |
| Oxidation resistance | Excellent | |
| Weather resistance | Excellent | |



WE CUT TAPE.

Learn more at capitaltape.com