



INDUSTRY AUTOMOTIVE RECREATIONAL VEHICLES GLAZING CONSTRUCTION DETAILING GASKETING **ACOUSTICS** LOG HOME MOUNTING PROTECTIVE

## TAPE OVERVIEW

Our VLD Foam Tape is a soft, low-density, closed-cell, PVC foam that is intended for general, industrial applications and is perfect for log cabin building.

- **Conforms to irregular surfaces**
- **Conforms to curves**
- **Seals, cushions, and dampens vibration and sound**
- **Withstands wear and abrasion.**
- **Excellent resistance to fungi**
- **Excellent resistance to weather**
- **Excellent resistance to oxidation**



### SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

## TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

<b>Density</b>	ASTM D-1667	6-8 lbs./cu. ft.
<b>Force to Compress (@ 25%)</b>	ASTM D-1667	2 PSI/14 kPa
<b>Compression Set (@ 25%)</b>	ASTM D-1667	8%
<b>Tensile Strength</b>	ASTM D-412	20 PSI/138 kPa
<b>Water absorption (% by volume)</b>	GTP	1.2
<b>Percent Elongation</b>	ASTM D-412	140
<b>Thermal Conductivity</b>	ASTM C-518	0.27
<b>Recommended Service Temp. 12 month shelf life</b>	-40°F to 180°F -40°C to 82°C	
<b>Recommended Application Temperature</b>	50°F to 110°F 10°C to 45°C	
<b>Fungi resistance</b>	Excellent	
<b>Oxidation resistance</b>	Excellent	
<b>Weather resistance</b>	Excellent	