

CT510

LOW-DENSITY CLOSED-CELL PVC FOAM TAPE



INDUSTRY AUTOMOTIVE RECREATIONAL VEHICLES GLAZING CONSTRUCTION DETAILING GASKETING ACOUSTICS LOG HOME MOUNTING PROTECTIVE

TAPE OVERVIEW

The CT510 tape is an extensive-use, closed-cell PVC industrial foam that is an excellent economical solution for applications where sealing out air, dust, and moisture are a must. Easy to compress and conform, yet incredibly strong—critical for sealing tight radius curves and irregular surfaces.

- Closed-cell PVC foam
- Lightweight, strong, and resilient
- Easy to compress and conformable
- Conforms to irregular surfaces and tight curves
- Excellent flame and chemical resistant properties
- Excellent resistance to fungi, oxidation, and weather



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	5 lbs./cu. ft.
Hardness (Shore OO)	ASTM D-2240	15 +/-5
Compression Deflection (@ 25%)	ASTM D-1667	1.5 +/- 2 PSI
Compression Set	LTM-028	10% max
Tensile Strength	ASTM D-412	15 PSI min
Percent Elongation	ASTM D-412	100 min
Low Temperature Flex	ASTM D-2136	No cracking
Recommended Service Temp. 12 month shelf life	-30°F to 200°F -35°C to 90°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	



WE CUT TAPE.

Learn more at capitaltape.com