

V810

LOW-DENSITY CLOSED-CELL PVC FOAM TAPE



INDUSTRY **AUTOMOTIVE** RECREATIONAL VEHICLES GLAZING **CONSTRUCTION DETAILING** GASKETING **ACOUSTICS** LOG HOME MOUNTING PROTECTIVE

TAPE OVERVIEW

The V810 Low-Density & Weatherstripping Tape from Capital Tape is an automotive-grade tape used when air- and moisture-tight seals on irregular surfaces are critical. Easy to compress, nearly impossible to destroy.

- Easy to compress and conformable
- Strong and resilient
- Ultra flexible to seal tight radius or irregular surfaces
- Excellent resistance to fungi, oxidation, and weather
- Fire rating: Meets/exceeds FMVSS 302A
- Self-Extinguishing



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	8 lbs./cu. ft.
Hardness (Shore OO)	ASTM D-2240	25
Force to Compress (@ 25%)	ASTM D-1667	2 PSI/14 kPa
Compression Set (@ 25%)	ASTM D-1667	4%
Tensile Strength	ASTM D-412	30 PSI/207 kPa
Peel Adhesion	ASTM D-1000	2 lbs
Water absorption (% by volume)	GTP	1.0
Percent Elongation	ASTM D-412	150
Thermal Conductivity	ASTM C-518	0.27
Recommended Service Temp. 12 month shelf life	-40°F to 180°F -40°C to 80°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	



WE CUT TAPE.

Learn more at capitaltape.com