

9223

RUBBER ADHESIVE POLYETHYLENE MOUNTING TAPE



INDUSTRY AUTOMOTIVE RECREATIONAL VEHICLES GLAZING CONSTRUCTION DETAILING GASKETING ACOUSTICS LOG HOME **MOUNTING** PROTECTIVE

TAPE OVERVIEW

This 1/32" thick polyethylene closed-cell foam mounting tape is coated on both sides with a permanent rubber-based adhesive ideal for bonding in indoor environments. Available in white or black.

- Ideal for mounting and joining
- Ideal for sealing applications
- Great for indoor bonding
- Very high shear strength
- Good initial tack

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Thickness	1/32"
Density	6.0 PCF
Tack	J. Dow No. 7
Peel Adhesion	123 oz/in PSTC-3
Shear Strength	Over 100 hrs. with 70.6 oz loading on 1" x 1" bonding 2 stainless steel plates at 77°F PSTC-9
Service Temperature	White 14°F to 122°F Black 14°F to 140°F



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.



WE CUT TAPE.

Learn more at capitaltape.com