CT1010

SWIRL-FREE MEDIUM DENSITY PVC FOAM TAPE



CATEGORY













STRUCTURAL SPACER

COMPRESSIBLE GLAZING

WEATHERSTRIPPING

RESIDENTIAL GLAZING

ULTRA HIGH-BOND

PE MOUNTING

INDUSTRY

AUTOMOTIVE

RECREATIONAL VEHICLES GLAZING

CONSTRUCTION DETAILING

GASKETING

ACOUSTICS

LOG HOME

MOUNTING

PROTECTIVE

TAPE OVERVIEW

Aggressive, pressure-sensitive adhesive on one side of a medium density, closed cell foam. Formulated to resist twisting and tearing, these tapes are popular in insulating and sealing products, ideal for applications in RV's and Semitrailers.

- Swirl-free/warp-free: It won't distort when penetrated by fasteners
- Flame resistant under FMVSS 302
- Seals out light, water, and dust
- · Ideal for mechanical and electronic
- Allows for easy die-cutting
- · Conforms to irregular surfaces
- Ideal applications: Recreational and offroad vehicles, vehicle overlap/truck roofline seals, die-cut gaskets, modular walls, railroad cars, marine, outdoor lighting fixtures and metal farm buildings, corrugated panels, lap joints



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	9-10 lbs./cu. ft.
Hardness (Shore 00)	ASTM D-2240	35
Force to Compress (@ 25%)	ASTM D-1667	4 PSI
Tensile Strength	ASTM D-412	40 PSI min
Percent Elongation	ASTM D-412	140% min
Compression Set	LTM-028	10% max
Low Temperature Flex	ASTM D-2136	No cracking
Recommended Service Temp. 12 month shelf life	-30°F to 200°F -35°C to 90°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	







WE CUT TAPE. Learn more at capitaltape.com



