CT610

LOW DENSITY PVC FOAM TAPE



CATEGORY













STRUCTURAL SPACER

COMPRESSIBLE GLAZING

WEATHERSTRIPPING

RESIDENTIAL GLAZING

ULTRA HIGH-BOND

PE MOUNTING

INDUSTRY

AUTOMOTIVE

RECREATIONAL VEHICLES GLAZING

CONSTRUCTION DETAILING

GASKETING

ACOUSTICS

LOG HOME

MOUNTING

PROTECTIVE

TAPE OVERVIEW

A closed-cell, low-density PVC foam tape manufactured for use in applications requiring dust, light, and water-tight seals, from electronics, weatherstripping, and recreational vehicles.

- · Low force compression, positive seal
- · Cold resistant, will not crack
- High flexibility for corners & curves
- Seals out light, water, and dust
- · Ideal for mechanical and electronic
- · Great for curtain walls, retail walls
- · Ideal applications: Recreational/ off-road vehicles, busses, retail weatherstripping and curtain wall, pneumatic seal, refrigeration, **HVAC** and electronic cabinet sealing, concrete walls (precast), telecommunications, environmentally-controlled rooms



SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Density	ASTM D-1667	6 lbs./cu. ft.
Hardness (Shore 00)	ASTM D-2240	18
Compression Deflection (@ 25%)	ASTM D-1667	1.7 PSI
Compression Set	ASTM D-1667	15% max
Tensile Strength	ASTM D-412	18 PSI min
Dimensional Stability	ASTM D-1667	5% max
Low Temperature Flex	ASTM D-2136	No cracking
Recommended Service Temp. 12 month shelf life	-40°F to 180°F -35°C to 90°C	
Recommended Application Temperature	50°F to 110°F 10°C to 45°C	
Fungi resistance	Excellent	
Oxidation resistance	Excellent	
Weather resistance	Excellent	







WE CUT TAPE. Learn more at capitaltape.com



