CT4745HTG

ULTRA-CLEAR, ULTRA-HIGH BOND TAPE

CapitalTape
A family business, since 1990

CATEGORY


STRUCTURAL SPACER


COMPRESSIBLE GLAZING


WEATHERSTRIPPING


RESIDENTIAL GLAZING


ULTRA HIGH-BOND

PE MOUNTING

INDUSTRY **AUTOMOTIVE** **RECREATIONAL VEHICLES** GLAZING CONSTRUCTION DETAILING GASKETING ACOUSTICS LOG HOME MOUNTING PROTECTIVE

TAPE OVERVIEW

The CT4745HTG is a grey, closed-cell acrylic foam tape offering extremely powerful long-term holding capability in both indoor and outdoor applications, often used in internal components and external manufacturing applications in a wide range of industries.

- **High temperature resistance**
- **Indoor/outdoor applications**
- **Ideal for internal components and external manufacturing applications**
- **Powerful long-term adhesion**
- **High shear strength**
- **Excellent weathering properties**

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Thickness	ASTM D412	.045" / 45 mil / 1.1mm
180° Adhesion*	PSTC-101 ASTM D-3330	Speed Load: 300mm/min Tape Size: 10mm Test Result: 2200gf
Dynamic Shear*	ASTM D-1002	Speed Load: 200mm/min Tape Size: 1.00cm^2 Test Result: 6.0 kgf/cm^2
Static Shear	ASTM D3654	73.4°F @ 3.3 lbs for 7 days: Passed 199.4°F@1.1 lb for 7 days: Passed
Temperature Resistance		Short Term: 450°F / 232°C Long Term: 300°F / 150°C

*Adhesion and Static Shear testing done on stainless steel

SCAN FOR MORE

Learn more, request samples, or get an online quote.

MEMBER NGA NATIONAL GLASS ASSOCIATION

FMVSS 302A Federal Motor Vehicle Safety Standard No. 302 CAPITAL TAPE

A.A.M.A. CERTIFIED 810.1-16 Type I

WE CUT TAPE. Learn more at capitaltape.com

1-888-888-TAPE service@capitaltape.com 4920 Commerce Parkway #11, Cleveland, OH 44128