CT4798T

CLOSED-CELL ACRYLIC FOAM TAPE

CapitalTape
A family business, since 1990

CATEGORY


STRUCTURAL SPACER


COMPRESSIBLE GLAZING


WEATHERSTRIPPING


RESIDENTIAL GLAZING


ULTRA HIGH-BOND

PE MOUNTING

INDUSTRY **AUTOMOTIVE** **RECREATIONAL VEHICLES** **GLAZING** **CONSTRUCTION DETAILING** GASKETING ACOUSTICS LOG HOME **MOUNTING** PROTECTIVE

TAPE OVERVIEW

The CT4798T is a clear, double-sided, high-performance, closed-cell acrylic foam tape designed for bonding of high and medium energy surfaces, as well as glass and various transparent plastics where a highly transparent bond is required and no stress corrosion may occur. Often used in internal components and external manufacturing applications in a wide range of industries.

- **High tack and shear strength**
- **Excellent chemical/solvent resistance**
- **Excellent UV light resistance**
- **Ideal for glass/transparent plastics**
- **Ideal for internal components**
- **Ideal for external manufacturing**

TAPE PROPERTIES

The values stated in charts are averages and are not to be construed as a warranty. Products must be tested by end user for application suitability.

Thickness		.098" / 98 mil
Length		54 ft / 18 yds
Density		56 lbs / ft^3 (900 kg / m^3)
90° Peel Adhesion*	ASTM D-3330	39 N/10mm (22 lbs/in^2)
Dynamic Shear*	ASTM D-1002	400 kPa (58 lbs/in^2)
Tensile Strength	ASTM D-897	440 kPa (64 lbs/in^2)
Static Shear 10,000 min. (7 days)	ASTM D-3654	22°C (72°F) – 1000 g/312mm^2 66°C (150°F) – 500 g/312mm^2 93°C (200°F) – 500 g/312mm^2

*Adhesion and Static Shear testing done on stainless steel

SCAN FOR MORE

Visit this product page, request samples, or get an online quote.

MEMBER NGA NATIONAL GLASS ASSOCIATION

FMVSS 302A Federal Motor Vehicle Safety Standard No. 302 CAPITAL TAPE

A.A.M.A. CERTIFIED 810.1-16 Type I

WE CUT TAPE. Learn more at capitaltape.com

1-888-888-TAPE service@capitaltape.com 4920 Commerce Parkway #11, Cleveland, OH 44128